


NOTE: BREAK ALL CORNERS WITH 0.015" (0.38 MM) RADIUS UNLESS OTHERWISE NOTED. STANDARD TOLERANCES TO APPLY UNLESS OTHERWISE SPECIFIED.

CUSTOMER PART No.	CUSTOMER <b>WOLVERINE STD</b>	WLV DIE No. <b>WS10387</b>	REV No. <b>0</b>
DESCRIPTION <b>1" x .125" THK. FLAT BAR</b>	QUOTE No. <b>19-1201-1</b>	PROPOSAL No. <b>S-11508</b>	



WALL THICKNESS .125 ± .007

DATE	REV	DESCRIPTION	BY
EST. AREA	.125	IN. <sup>2</sup>	EST. AREA 80.645
EST. WT.	.146	LBS/FT.	EST. WT. .217
EST. PER.	2.250	IN.	EST. PER. 57.150
OUT PER.		IN.	OUT PER.
C.C.D.	1.008	IN.	C.C.D. 25.603
FACTOR 15.5	FINISH M/F	ALLOY & TEMP. 6061	
CKD BY	SCALE 1:1	DWN BY <b>B.A.</b>	DATE 3/29/19

**WOLVERINE** 2100 MARKET STREET  
 DECATUR, AL 35816  
 800-633-3972

THIS DRAWING IS NOT NECESSARILY A COPY OF YOUR ORIGINAL. PLEASE APPROVE DIMENSIONS AND TOLERANCES INDICATED. WOLVERINE ASSUMES NO RESPONSIBILITY EITHER TECHNICAL OR LEGAL FOR HAVING THIS SHAPE MADE. THE CUSTOMER AGREES TO FULLY PROTECT WOLVERINE FROM CLAIMS OF OTHERS RESULTING FROM THIS SHAPE.

**SIGNED:** \_\_\_\_\_ **DATE:** \_\_\_\_\_

**PRINT NAME:** \_\_\_\_\_