


NOTE: BREAK ALL CORNERS WITH 0.015" (0.38 MM) RADIUS UNLESS OTHERWISE NOTED. STANDARD TOLERANCES TO APPLY UNLESS OTHERWISE SPECIFIED.

CUSTOMER PART No.	CUSTOMER WOLVERINE STD	WLV DIE No. WS10417	REV No. 0
DESCRIPTION 1/4 x 1-1/2 FLAT BAR		QUOTE No. 19-1212-2	PROPOSAL No. S-11546



WALL THICKNESS .250 ± .008

DATE	REV	DESCRIPTION	BY
EST. AREA	.375	IN. ²	EST. AREA 241.935
EST. WT.	.439	LBS/FT.	EST. WT. .653
EST. PER.	3.500	IN.	EST. PER. 88.900
OUT PER.		IN.	OUT PER.
C.C.D.	1.521	IN.	C.C.D. 38.633
FACTOR 8	FINISH M/F	ALLOY & TEMP.	6061
CKD BY	SCALE 1:1	DWN BY B.A.	DATE 4/1/19

WOLVERINE

2100 MARKET STREET
DECATUR, AL 35816
800-633-3972

THIS DRAWING IS NOT NECESSARILY A COPY OF YOUR ORIGINAL. PLEASE APPROVE DIMENSIONS AND TOLERANCES INDICATED. WOLVERINE ASSUMES NO RESPONSIBILITY EITHER TECHNICAL OR LEGAL FOR HAVING THIS SHAPE MADE. THE CUSTOMER AGREES TO FULLY PROTECT WOLVERINE FROM CLAIMS OF OTHERS RESULTING FROM THIS SHAPE.

SIGNED: _____ DATE: _____

PRINT NAME: _____