


NOTE: BREAK ALL CORNERS WITH 0.015" (0.38 MM) RADIUS UNLESS OTHERWISE NOTED. STANDARD TOLERANCES TO APPLY UNLESS OTHERWISE SPECIFIED.

CUSTOMER PART No.	CUSTOMER WOLVERINE STD	WLV DIE No. WS10566	REV No. 0
DESCRIPTION 3/8" x 4" FRE BAR		QUOTE No. 19-1526-8	PROPOSAL No. S-12391



WALL THICKNESS .375 ± .008

DATE	REV	DESCRIPTION	BY
EST. AREA	1.470	IN. ²	EST. AREA 948.385
EST. WT.	1.720	LBS/FT.	EST. WT. 2.560
EST. PER.	8.428	IN.	EST. PER. 214.071
OUT PER.		IN.	OUT PER.
C.C.D.	4.000	IN.	C.C.D. 101.600
FACTOR 5	FINISH M/F	ALLOY & TEMP.	
CKD BY	SCALE 1:1	DWN BY B.A.	DATE 9/19/19

WOLVERINE

2100 MARKET STREET
DECATUR, AL 35816
800-633-3972

THIS DRAWING IS NOT NECESSARILY A COPY OF YOUR ORIGINAL. PLEASE APPROVE DIMENSIONS AND TOLERANCES INDICATED. WOLVERINE ASSUMES NO RESPONSIBILITY EITHER TECHNICAL OR LEGAL FOR HAVING THIS SHAPE MADE. THE CUSTOMER AGREES TO FULLY PROTECT WOLVERINE FROM CLAIMS OF OTHERS RESULTING FROM THIS SHAPE.

SIGNED: _____ DATE: _____
PRINT NAME: _____